

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number
WO 2004/111369 A1

(51) International Patent Classification⁷: **E05B 27/06**

(21) International Application Number:
PCT/AU2004/000779

(22) International Filing Date: 11 June 2004 (11.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003903029 16 June 2003 (16.06.2003) AU
2004200498 9 February 2004 (09.02.2004) AU
531575 8 March 2004 (08.03.2004) NZ

(71) Applicant (for all designated States except US): **PRE-
DESIGN PTY LTD** [AU/AU]; 9 Victoria Street, Ger-
ringong, NSW 2534 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **PREDDEY, Brian,**
Francis [—/AU]; 9 Victoria Street, Gerringong, NSW
2534 (AU).

(74) Agent: **WATERMARK PATENT & TRADEMARK**
ATTORNEYS; Building 1 Binary Centre, Riverside
Corporate Park, 3 Richardson Place, Nprth Ryde, NSW
2113 (AU).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: **ROTARY LOCK AND KEY**



(57) Abstract: A cylinder lock is provided. The lock includes a rotor assembly (17) having a combination post (12) as a core. The combination post (12) has combination holes arranged thereon which define the combination of the lock. The rotor assembly (17) includes locking bars having pins (15) directed radially towards the combination post (12). The locking bars are displaceable in an axial position by an appropriately coded key until each pin (15) is directed towards a respective combination hole. Turning the key causes the rotor assembly (17) to rotate. At various rotational positions, the locking bars are displaced radially causing the pins (15) to engage their respective combination holes. The combination post (12) can be provided with parallel combination holes. Furthermore, the combination post (12) can be removable in order to replace the combination post (12) with another post having different combination values, thereby changing the combination of the lock.

WO 2004/111369 A1

BEST AVAILABLE COPY

Express Mail Label No.
EV 291959890 US



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.